

GUANGDONG ORUN PETROCHEMICAL CO., LTD
TEL: +86 757 81264752
Internet: <http://www.terzo-tech.com>
E-mail: info@terzo-tech.com

Gas engine oil 15W-40

Description

TERZO Gas engine oil 15W-40 have been developed for application in highly stressed gasoline and diesel gas engines, including turbo charged units. High neutralisation potential guarantees reliable protection against corrosion and wear in operation with combustion gases containing large amounts of sulphur and hydrogen sulphides, such as sewer, bio gases and untreated natural gases. Ash-containing well-balanced detergent and dispersant additives prevent undesirable build-up of sludge and varnish in the crankcase and combustion chambers. corresponds to the requirements of leading gas engine manufacturers and is also suitable for operation with catalytic converters.

Application

TERZO Gas engine oil 15W-40 is approved by Jenbacher for the series 2 and 3, Cummins and by Hagl for the operation with special gases. In addition to this TERZO Gas engine oil 15W-40 corresponds to the requirements of leading gas engine manufacturers and is suitable for the operation of gas engines with catalytic converters, too

Specifications

Cummins CES 20092 ;
DDC 93K216 ;

Typicals

Density at 15 °C, kg/l	0,890
Viscosity 40 °C, mm²/s	132
Viscosity 100 °C, mm²/s	13,5
Viscosity Index	97
Flash Point COC, °C	272
Pour Point, °C	-21
Total Base Number, mgKOH/g	8,8
Sulphate Ash, %	0,88