

GUANGDONG ORUN PETROCHEMICAL CO., LTD
TEL: +86 757 81264752
Internet: <http://www.terzo-tech.com>
E-mail: info@terzo-tech.com

Specialsynth 5W40

Description

This full-synthetic fuel economy universal motor oil is produced with high quality solvent refined base oils and a number of additives, to obtain the following properties:

- a high detergency and dispersion power
- a strong resistance against oxidation
- effective in preventing from wear, corrosion and foam
- a high and stable viscosity index

Application

Suitable lubricating oil for gasoline engines under light service conditions, moreover for diesel engines of passenger cars and for light delivery vans in light service. Not applicable for turbo-charging diesel engines for which a minimum API CG level oil is required.

Specifications

Performance level:
API SP
ACEA A3/B4
VW502.00 AND 505.00
MB229.3
Porsche A40
BMW LONGLIFE 01
MB-Blatt 226.5
Opel GM-LL-B-025
Renault RN 0700 and RN 0710

Typicals

Density at 20 °C, kg/l	0,848
Viscosity -30 °C, mPa.s	5627
Viscosity 40 °C, mm²/s	88,27
Viscosity 100 °C, mm²/s	13,7
Viscosity Index	165
Flash Point COC, °C	232
Pour Point, °C	-39
Total Base Number, mgKOH/g	7,2
Sulphate Ash, %	0.78