Product Information ORUN-071

GUANGDONG ORUN PETROCHEMICAL CO., LTD
TEL: +86 757 81264752
Internet: http://www.terzo-tech.com
E-mail: info@terzo-tech.com

SynthGen 10W30

Description

This motor oil is based on high quality solvent refined mineral and synthetic base oils.By adding a well balanced choice of additives the following properties are obtained:
- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a good detergency and dispersion
- a safe lubrication film at high temperatures
- a strong protection against wear, corrosion and foaming

Application

This all-round motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

Specifications

Performance level:
API SL/SN

Typicals

Density at 20 °C, kg/l	0,861
Viscosity -25 °C, mPa.s	3850
Viscosity 40 °C, mm²/s	75,00
Viscosity 100 °C, mm²/s	12,15
Viscosity Index	160
Flash Point COC, °C	220
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,3
Sulphate Ash, %	1,33

24/03/2025

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.
You can download a recent material safety data sheet of this product on our website..