

GUANGDONG ORUN PETROCHEMICAL CO., LTD
 TEL: +86 757 81264752
 Internet: <http://www.terzo-tech.com>
 E-mail: info@terzo-tech.com

Trans ATF JP

Description

A very high graded fully synthetic automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- a very strong dispersion, therefore sludge is restricted to a minimum
- a very low pour point
- very good stability against oxidation and thermal properties
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured.

Application

This fluid may be used for automatic gear boxes (including hybrid), power steering units, torque converters and other equipment, for which an ATF is required, which exceeds ATF Dexron III and II. Its special composition causes a longer lifetime of this liquid compared with older Dexron types. This multi-vehicle ATF meets the hardware protection of the specified low viscosity fluids, like AW-2. This product cannot be used in DCT's and CVT's or when an oil with the Ford Type F/G specification is recommended.

Specifications

Performance level:

- Dexron III-H
- Aisin Warner JWS 3309 (T-IV)
- Allison C-4
- Daihatsu Ammix ATF D3-SP
- JASO M315 Type 1A
- Honda ATF Z-1
- Hyundai /Kia SP-III
- Isuzu BESCO ATF II, ATF III
- Mazda ATF M-III, M-V
- Mitsubishi SP-II, SP-III DiaQueen WS
- Nissan Matic Fluid C, D, J
- Toyota Autofluid D-II, D-III
- Toyota Type T-IV
- Toyota WS

Typicals

Density at 20 °C, kg/l	0,85
Viscosity 40 °C, mm²/s	36,26
Viscosity 100 °C, mm²/s	7,28
Viscosity Index	165
Flash Point COC, °C	222
Pour Point, °C	-45
Total Base Number, mgKOH/g	2,8

01/08/2024

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website..