Product Information ORUN-038

GUANGDONG ORUN PETROCHEMICAL CO., LTD
TEL: +86 757 81264752
Internet: http://www.terzo-tech.com
E-mail: info@terzo-tech.com

4T Super 5W40

Description

A special fully synthetic four-stroke engine oil developed for use under extreme low temperatures. This oil is specially designed for use under arctic conditions. The product is based on a combination of synthetic base oils, among others ester and highly advanced additives. This engine oil has through its composition a high resistance to oxidation and viscosity loss under high load and ensures a good flow behavior at low temperatures. This engine oil has the following typical properties:

- a very low tendency to evaporation
- a high and very stable viscosity index
- a good resistance against shearing
- a high resistance against aging
- a safe lubrication film at low and very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Application


A fully synthetic four-stroke engine oil, designed for motorcycles under race conditions at low temperatures. This oil has proven its quality in engine tests and under the most extreme conditions at very low temperatures.

Specifications

Performance level:
API SN
JASO MA2
JASO MA

Typicals

Density at 15 °C, kg/l	0,848
Viscosity -25 °C, mPa.s	3901
Viscosity 40 °C, mm²/s	88,10
Viscosity 100 °C, mm²/s	14,00
Viscosity Index	167
Flash Point COC, °C	261
Pour Point, °C	-42
Total Base Number, mgKOH/g	6.1



01/08/2024

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website..