



GUANGDONG ORUN PETROCHEMICAL CO., LTD  
TEL: +86 757 81264752  
Internet: <http://www.terzo-tech.com>  
E-mail: [info@terzo-tech.com](mailto:info@terzo-tech.com)

## MULTIPURE Top 5W-30

### Description

A fuel economy, synthetic, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- mid SAPS content
- suitable for modern catalysts
- a fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### Application

This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

### Specifications

Performance level:  
ACEA C3 API SQ  
Approved under  
VW 504.00/507.00  
MB-Approval 229.31/229.51  
BMW Longlife-04  
Porsche C30  
Meets the requirements of:  
MB 229.52  
Opel OV0401547

### Typicals

|                            |       |
|----------------------------|-------|
| Density at 20 °C, kg/l     | 0,853 |
| Viscosity -30 °C, mPa.s    | 5980  |
| Viscosity 40 °C, mm²/s     | 69,8  |
| Viscosity 100 °C, mm²/s    | 12,3  |
| Viscosity Index            | 176   |
| Flash Point COC, °C        | 224   |
| Pour Point, °C             | -45   |
| Total Base Number, mgKOH/g | 8,3   |
| Sulphate Ash, %            | 0,75  |
| HTHS viscosity@150, mPa.s  | 3,7   |



01/08/2024

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website..

