

Specialsynth 5W40

Description

This full-synthetic fuel economy universal motor oil is produced with high quality solvent refined base oils and a number of additives, to obtain the following properties:

- a high detergency and dispersion power
- a strong resistance against oxidation
- effective in preventing from wear, corrosion and foam
- a high and stable viscosity index

Application

Suitable lubricating oil for gasoline engines under light service conditions, moreover for diesel engines of passenger cars and for light delivery vans in light service. Not applicable for turbo-charging diesel engines for which a minimum API CG level oil is required.

Specifications

Performance level:
 API SQ
 ACEA A3/B4
 VW502.00 AND 505.00
 MB229.3
 Porsche A40
 BMW LONGLIFE 01
 MB-Blatt 226.5
 Opel GM-LL-B-025
 Renault RN 0700 and RN 0710

Typicals

Density at 20 °C, kg/l	0,848
Viscosity -30 °C, mPa.s	5627
Viscosity 40 °C, mm²/s	88,27
Viscosity 100 °C, mm²/s	13,7
Viscosity Index	165
Flash Point COC, °C	232
Pour Point, °C	-39
Total Base Number, mgKOH/g	7,2
Sulphate Ash, %	0.78



01/08/2024

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website..

