



GUANGDONG ORUN PETROCHEMICAL CO., LTD
TEL: +86 757 81264752
Internet: <http://www.terzo-tech.com>
E-mail: info@terzo-tech.com

SuperSynth 0W-16

Description

A fuel economy SAE 0W16 motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and stable viscosity index
- a good resistance against shearing
- a very fast cold start, even at very low temperatures
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Application

This fuel economy, specially composed SAE 0W16 motor oil, is recommended for use in petrol engines in passenger cars of Japanese OEMs, equipped with the latest techniques. API SQ Resource Conserving

Specifications

API SQ
ILSAC GF-7B

Typicals

Density at 15 °C, kg/l	0,845
Viscosity -35 °C, mPa.s	5600
Viscosity 40 °C, mm²/s	37,40
Viscosity 100 °C, mm²/s	7,34
Viscosity Index	166
Flash Point COC, °C	224
Pour Point, °C	-45
Total Base Number, mgKOH/g	8,5
Sulphate Ash, %	0,89



01/08/2024

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website..

