



GUANGDONG ORUN PETROCHEMICAL CO., LTD
TEL: +86 757 81264752
Internet: <http://www.terzo-tech.com>
E-mail: info@terzo-tech.com

SuperSynth 0W40

Description

A modern, Fully synthetic, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

A universal, special composed fully synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

Specifications

Performance level:
ACEA A3/B4
API SQ
BMW Longlife-04
MB 229.3/229.5
Porsche A40
VW 502.00/505.00

Typicals

Density at 20 °C, kg/l	0,841
Viscosity -35 °C, mPa.s	5107
Viscosity 40 °C, mm²/s	73,57
Viscosity 100 °C, mm²/s	13,57
Viscosity Index	190
Flash Point COC, °C	230
Pour Point, °C	-45
Total Base Number, mgKOH/g	12,2
Sulphate Ash, %	1,12
HTHS viscosity@150, mPa.s	3,8



01/08/2024

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website...

