



GUANGDONG ORUN PETROCHEMICAL CO., LTD
TEL: +86 757 81264752
Internet: <http://www.terzo-tech.com>
E-mail: info@terzo-tech.com

Tor Multisynth 15W-40

Description

A universal multigrade engine oil produced with special selected solvent refined base oils and additives. This engine oil has the following properties:

- a very good detergency prevents deposits in the engine
- a very good dispersion that prevents from precipitation and sludge
- a powerful action against wear, corrosion and foam
- a stable viscosity index
- suitable for extended drain intervals

Application


This universal lubricating oil is suitable for gasoline or diesel engines, with or without super-charging. This motor oil is suitable for application in mixed fleets.

Specifications

API CI-4/SL
ACEA E7
Cummins CES20076/20072/20071
MB 228.3
Mack EO-M+
MAN 3275
Volvo VDS-2
MTU type 2

Typicals

Density at 15 °C, kg/l	0,882
Viscosity -20 °C, mPa.s	5765
Viscosity 40 °C, mm²/s	110,50
Viscosity 100 °C, mm²/s	14,87
Viscosity Index	136
Flash Point COC, °C	234
Pour Point, °C	-30
Total Base Number, mgKOH/g	10.2
Sulphate Ash, %	1.1



01/08/2024

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website..

